




SINGLE COUNTERBALANCE VALVES FOR OPEN CENTER

BSA counterbalance valves (NPTF thread) are used to keep a load locked, the built-in relief valve protects the system from overpressure in the cylinder by draining the oil.



HYDRAULIC CIRCUIT



TECHNICAL CHARACTERISTICS

F	H	B	Ø D	L	M	P	Q	R	S	T
3/8 NPTF	50 [1,97]	30 [1,18]	8,5 [0,33]	95 [3,74]	82 [3,22]	23 [0,91]	66 [2,60]	43 [1,70]	7 [0,28]	50 [1,97]
1/2 NPTF	60 [2,36]			100 [3,94]	85 [3,34]	21 [0,83]	67,5 [2,66]	50 [1,97]	10 [0,39]	49 [1,93]
Steel body (on request aluminium body – stainless steel AISI 316L body)										

PERFORMANCES



OPTIONAL TAMPER PROOF CAP M10



CODE
62200021

ORDERING CODE

CODE	TYPE	F ports	MAX FLOW l/min [usgpm]	MAX PRESSURE bar [PSI]	STANDARD SETTING bar [PSI]	RANGE SPRING bar [PSI]	INCREASE TO TURN bar [PSI]	PILOT RATIO	WEIGHT kg [lb]
FA1134	BSA2N21	3/8 NPTF	40 [10,6]	350 [5075]	210 [3045]	30/210 [435/3045]	80 [1160]	1:4,25 On request 1:8,1	1,05 [2,31]
FA1135	BSA2N35				350 [5075]	60/350 [870/5075]	135 [1960]		
FA1136	BSA3N21	1/2 NPTF	60 [15,9]		210 [3045]	30/210 [435/3045]	80 [1160]		1,25 [2,76]
FA1137	BSA3N35				350 [5075]	60/350 [870/5075]	135 [1960]		
Standard setting 350 bar [5075 PSI] to 5 l/m [1,32 USgpm]					Standard setting 210 bar [3045 PSI] to 5 l/m [1,32 USgpm]				