



DOUBLE ACTING PILOT CHECK VALVES

VBD pilot check valves are used to lock a double acting actuator in place in both directions, ensuring the load is locked



HYDRAULIC CIRCUIT





TECHNICAL CHARACTERISTICS

mm [Inches]

F	B	H	L	M	N	P	A	C	D	E
SAE 6 [9/16-18 UNF]	30 [1,18]	40 [1,57]	63 [2,5]	16,5 [0,65]	46,5 [1,83]	7 [0,27]	24,5 [0,96]	87,5 [3,44]	31,5 [1,24]	M8
SAE 8 [3/4-16 UNF]		45 [1,77]	66 [2,6]	15 [0,59]	51 [2]	6 [0,23]	28 [1,10]	94 [3,70]	33 [1,3]	d.7 [0,27]
		50 [1,97]	80 [3,15]	20 [0,79]	60 [2,36]	15 [0,59]	31,5 [1,24]	111,5 [4,39]	40 [1,57]	8,5 [0,33]
Steel body										

PERFORMANCES



ORDERING CODE

CODE	TYPE	F ports	MAX FLOW l/min [USgpm]	MAX PRESSURE bar [PSI]	PILOT RATIO	CRACKING PRESSURE bar [PSI]	WEIGHT kg [lb]
FA5029	VBD1S	SAE 6	20 [5,3]	350 [5075]	1:5,5	4,5 [65]	0,63 [1,39]
FA5030	VBD2S	SAE 8	35 [9,2]				0,6 [1,32]
FA5059	VBD2SH		50 [13,2]		1:5		1 [2,20]