

# DSE5


## DIRECTIONAL VALVE WITH PROPORTIONAL CONTROL

### SERIES 10

#### SUBPLATE MOUNTING ISO 4401-05

**p** max 320 bar  
**Q** max 90 l/min

#### MOUNTING INTERFACE




#### PERFORMANCES


(obtained with mineral oil with viscosity of 36 cSt at 50°C and electronic control card)

Maximum operating pressure: - P - A - B ports - T port : standard version version with Y port	bar	320 210 320
Maximum flow with $\Delta p$ 10 bar P-T	l/min	30 - 60
Step response	see paragraph 6	
Hysteresis (with PWM 100 Hz)	% of Q max	< 6%
Repeatability	% of Q max	< $\pm 1,5\%$
Electrical characteristics	see paragraph 5	
Ambient temperature range	°C	-20 / +60
Fluid temperature range	°C	-20 / +80
Fluid viscosity range	cSt	10 ÷ 400
Fluid contamination degree	According to ISO 4406:1999 class 18/16/13	
Recommended viscosity	cSt	25
Mass: single solenoid valve double solenoid valve	kg	4,4 5,9

#### OPERATING PRINCIPLE



#### HYDRAULIC SYMBOLS (typical)



## 1 - IDENTIFICATION CODE

<b>D</b>	<b>S</b>	<b>E</b>	<b>5</b>	<b>-</b>					<b>/ 10</b>	<b>-</b>			<b>/</b>	
----------	----------	----------	----------	----------	--	--	--	--	-------------	----------	--	--	----------	--

Directly operated directional control valve

Electric proportional control

Size ISO 4401-05

Spool type:  
**C** = closed centers  
**A** = open centers

Spool nominal flow (see table 2)

Solenoid position (omit for configuration with two solenoids):  
**SA** = 1 solenoid on side A  
**SB** = 1 solenoid on side B

Option:  
**/ W7** = Zinc-nickel surface treatment (see **NOTE**)  
 Omit if not required

Option: manual override (see at par. 9)

Coil electrical connection:  
 plug for connector type  
 DIN 43650 (**standard**)

**D12** = Nominal solenoid voltage 12V DC  
**D24** = Nominal solenoid voltage 24V DC

Seals:  
**N** = NBR seals for mineral oil (**standard**)  
**V** = FPM seals for special fluids

Series No. (from 10 to 19 sizes and mounting dimensions remain unchanged)

**NOTE:** The standard valve is supplied with surface treatment of phosphating black.

The zinc-nickel finishing makes the valve suitable to ensure a salt spray resistance up to 240 hours (test operated according to EN ISO 9227 standards and test evaluation operated according to UNI EN ISO 10289 standards).

## 2 - CONFIGURATIONS

Valve configuration depends on the combination of the following elements:  
 number of proportional solenoids, spool type, nominal flow rate.

2 solenoids configuration:  
 3 positions with spring centering

“SA” configuration: 1 solenoid on side A.  
 2 positions (central + external) with spring centering

“SB” configuration: 1 solenoid on side B.  
 2 positions (central + external) with spring centering


<b>*</b>	Controlled flow with $\Delta p$ 10 bar P-T
<b>30</b>	30 l/min
<b>60</b>	60 l/min
<b>60/30</b>	60 (P-A) / 30 (B-T) l/min

### 3 - CHARACTERISTIC CURVES



(values measured with oil viscosity of 36 cSt at 50°C and with electronic control unit)

Typical constant flow rate control curves at  $\Delta p$  according to current supply to solenoid (D24 version, maximum current 1600 mA), measured for the various spools types available.



The reference  $\Delta p$  values are measured between ports P and T on the valve.





**SPOOL TYPE C30**



**SPOOL TYPE C60**





**SPOOL TYPE A30**





### SPOOL TYPE A60



www.sumy.ir

### 4 - HYDRAULIC FLUIDS

Use mineral oil-based hydraulic fluids HL or HM type, according to ISO 6743-4. For these fluids, use NBR seals (code N). For fluids HFDR type (phosphate esters) use FPM seals (code V). For the use of other fluid types such as HFA, HFB, HFC, please consult our technical department. Using fluids at temperatures higher than 80 °C causes a faster degradation of the fluid and of the seals characteristics. The fluid must be preserved in its physical and chemical characteristics.

### 5 - ELECTRICAL CHARACTERISTICS

#### Proportional solenoid

The proportional solenoid comprises two parts: tube and coil. The tube, screwed to the valve body, contains the armature which is designed to maintain friction to a minimum thereby reducing hysteresis. The coil is mounted on the tube secured by means of a lock nut. It can be rotated through 360° depending on installation clearances.

<b>NOMINAL VOLTAGE</b>	VDC	<b>12</b>	<b>24</b>
<b>RESISTANCE</b> (at 20°C)	Ω	3 - 3.4	8.65
<b>MAXIMUM CURRENT</b>	A	2.6	1.6
<b>DUTY CYCLE</b>	100%		
<b>ELECTROMAGNETIC COMPATIBILITY (EMC)</b>	according to 2004/108/EC		
<b>CLASS OF PROTECTION:</b> atmospheric agents (IEC 60529) coil insulation (VDE 0580) Impregnation	IP 65 class H class F		

### 6 - STEP RESPONSE

(measured with mineral oil with viscosity of 36 cSt at 50°C and with electronic control unit)

Step response is the time taken for the valve to reach 90% of the set position value following a step change of reference signal. The table shows typical response times tested with spool type C60 and  $\Delta p = 20$  bar P-T.


<b>REFERENCE SIGNAL STEP</b>	0→100%	100%→0
Step response [ms]		
<b>DSE5-A*</b> <b>DSE5-C*</b>	50	40

### 7 - INSTALLATION


DSE5 valves can be installed in any position without impairing correct operation.

Ensure that there is no air in the hydraulic circuit.

Valves are fixed by means of screws or tie rods on a flat surface with planarity and roughness equal to or better than those indicated in the relative symbols. If minimum values are not observed fluid can easily leak between the valve and support surface.




## 8 - OVERALL AND MOUNTING DIMENSIONS



## 9 - VERSIONS WITH EXTERNAL DRAIN PORT

### 9.1 - Identification Code




These versions allow the operation with pressures up to 320 bar on T port of the valve .

The additional drain port is connected with the solenoid chamber in this way the tubes are not stressed by the pressure operating on the T port of the valve.

### 9.2 - Y Version


The drain port Y is realized on the valve mounting surface in compliance with ISO 4401-05-05-0-05 standard.

There is no X port.



### 9.3 - L version

It consists of a drain port on the mounting surface of the valve according to ISO 4401-05-06-0-05 standard




## 10 - MANUAL OVERRIDE

The standard valve has solenoids whose pin for the manual operation is integrated in the tube. The operation of this control must be executed with a suitable tool, minding not to damage the sliding surface.

The following manual override is available upon request:

- **CK** version, knob. When the set screw is screwed and its point is aligned with the edge of the knob, tighten the knob till it touches the spool: in this position the override is not engaged and the valve is de-energized. After adjusting the override, tighten the set screw in order to avoid the knob loosening.



## 11 - ELECTRONIC CONTROL UNITS

### DSE5- \*\*SA (SB)

<b>EDC-131</b>	for solenoid 24V DC	plug version	see catalogue 89 120
<b>EDC-151</b>	for solenoid 12V DC		
<b>EDM-M131</b>	for solenoid 24V DC	DIN EN 50022 rail mounting	see catalogue 89 250
<b>EDM-M151</b>	for solenoid 12V DC		

### DSE5- A\*    DSE5-C\*

<b>EDM-M231</b>	for solenoid 24V DC	DIN EN 50022 rail mounting	see catalogue 89 250
<b>EDM-M251</b>	for solenoid 12V DC		

## 12 - SUBPLATES

(see cat. 51 000)

Type PMD4-AI4G with rear ports 3/4" BSP
Type PMD4-AL4G with side ports 1/2" BSP